



15 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420

Tel: + 27 21 510 5811

Fax: + 27 21 510 5818

www.classiqcolours.com

vanessa@classiqcoatings.com

orders@classiqcoatings.com

admin@classiqcoatings.com

(Technical)

(Orders)

(Admin)

CLASSIQ INK SERIES

MULTI-PURPOSE FLEXO LAMINATION INK FOR HIGH QUALITY REVERSE PRINTING ON PVDC COATED POLYESTER AND TREATED POLYESTER (PET)

FEATURES

- High Quality Reverse Printing with Excellent Mileage
- Outstanding Adhesion on PET
- Suitable for Line and Half tone work
- Excellent Bond strengths achieved between PET/LDPE constructions
- Elimination of Ink splitting
- Suitable for Solvent Based and Solvent Free lamination
- Low solvent retention and odour
- TAA free

PROPERTIES

- | | |
|---------------------|--|
| ▪ Package Viscosity | 35-40 sec. Zahn Cup No. 2 @ 25 degrees C |
| ▪ Reducer | Ethanol |
| ▪ Retarder | Ethoxy Propanol |
| ▪ Wash Up | Mixture of ethanol and ethyl acetate |
| ▪ Flash Point | < 25° C |

DRYING

A drying temperature of 65-75°C is sufficient to achieve adhesion to filmic substrates, although temperatures may need to be adjusted outside this range, due to variations in substrates, process and press conditions.

PACKAGING AND STORAGE

Packed in 25 kg pails or 200 kg drums. Storage stability is six months in original, unopened containers at 20°C. After use, containers should be tightly closed to improve shelf life.

GENERAL

The Classiq Ink Series is available in Process and Pantone Colours and all our products are manufactured according to ISO9001:2008 quality standards.

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR JUNE 2017